

PRODUCT DETAILS					
		Plank / Tile Size (Nominal)	7" x 48" (177.8 mm x 1219.2 mm)	18" x 18" (455 mm x 455 mm)	6" x 23.6" (600 mm x 600 mm)
Overall Product Thickness	2.5 mm (0.1 In.)				
Wear Layer Thickness	0.5 mm (20mil)	Pieces per Carton	18	19	14
Finish	Uthethane with Ceramic Bead	Square Feet per Carton	42 SF	42.3	54.15
Warranty	15 Year Limited Commercial	Carton Weight	34.5 Lbs. (15.7 Kg)	35.2 Lbs. (16 Kg)	46.3 Lbs. (22 Kg)
		Cartons per Pallet	50	52	48
Note: 18" x 18" tile must be quarter turned to avoid shading concerns.		Square Feet per Pallet	2,100.0 SF	2201.7 SF	2599.1 SF
		Pallets per Container	20	20	18
		Square Feet per Container	42,000.0 SF	44,033.5 SF	46,784.6 SF

**TEST METHOD**

Requirements		
<b>ASTM F1700 STANDARD SPECIFICATION FOR SOLID VINYL FLOOR TILE</b>	Class III - Print Film Vinyl Tile, Type B - Embossed Surface	Meets Requirements
<b>ASTM F137 Flexibility</b>	25.4 mm Mandrel	Meets Requirements
<b>ASTM F386 Flooring Thickness</b>	as specified +/- 0.005 in. (0.13)	Meets Requirements
<b>ASTM F410 Wear Layer Thickness</b>	Commercial 20 Mils (0.020 in. or 0.5 mm) min.	Meets Requirements
<b>ASTM F925 Resistance to Chemicals</b>	Passes No or slight discoloration	Meets Requirements
<b>ASTM F1514 Heat Color Stability</b>	Passes Delta E ≤ 8.0	Meets Requirements
<b>ASTM F1515 Light Color Stability</b>	Passes Delta E ≤ 8.0	Meets Requirements
<b>ASTM F1914 Short Term Indentation</b>	Avg. Residual Indentation < 8.0% Max. Residual Indentation < 10.0%	Meets Requirements
<b>ASTM F2055 Size</b>	Max. +/- 0.016 in. (0.4 mm) per linear ft. (305 mm)	Meets Requirements
<b>ASTM F2055 Squareness</b>	Max. 0.01 In. (0.25 mm)	Meets Requirements
<b>ASTM F2199 Dimensional Stability</b>	Max 0.02 in. (0.5 mm) per linear ft.	Meets Requirements
<b>ASTN F2199 Curling</b>	Max 0.079 in. (2.0 mm)	Meets Requirements

**PERFORMANCE TEST DATA**

<b>ASTM E648 (NFPA 253) Critical Radiant</b>	Class 1 ≥ 0.45 W/cm2	Meets Requirements
<b>ASTM E662 (NFPA 258) Smoke Density</b>	< 450 Flaming / Non-Flaming	Meets Requirements
<b>ASTM F970 Static Load Limit</b>	250 psi Passes Commercial Requirement	Meets Requirements
<b>ASTM F970 Static Load Limit</b>	1,200 psi Maximum at 0.005 Residual Indentation	Meets Requirements
<b>ASTM D2047 Slip Resistance</b>	≥ 0.6 DCOF - ADA Compliant	Meets Requirements

**SUSTAINABILITY TEST DATA**

<b>FloorScore Certified</b>	Yes	Meets Requirements
<b>LEED Contribution MR Credit</b>	Building Product Disclosure - Environmental Product Declaration	Meets Requirements
<b>LEED Contribution MR Credit</b>	Building Product Disclosure, Material Ingredients - Health Product Declaration	Meets Requirements
<b>LEED Contribution EQ Credit</b>	Low-Emitting Materials - FloorScore (CPDH Method v1.2-2017)	Meets Requirements
<b>Recycled Content</b>	100% Post Industrial	