

PRODUCT DETAILS						
Overall Product Thickness	2.5 mm (0.1 In.)	Plank / Tile Size (Nominal)	7" x 48" (177.8 mm x 1219.2 mm)	18" x 18" (457.2 mm x 457.2 mm)	18" x 36" (457.2 mm x 914.4 mm)	23.6" x 23.6" (600 mm x 600 mm)
Wear Layer Thickness	0.5 mm (20mil)	Pieces per Carton	18	19	12	14
Finish	High Performance Uthethane with Ceramic Bead	Square Feet per Carton	42 SF	42.3	54 SF	54.15
Antimicrobial	Ultrafresh	Carton Weight	34.5 Lbs. (15.7 Kg)	35.2 Lbs. (16 Kg)	44.1 Lbs. (20 Kg)	46.3 Lbs. (22 Kg)
Edge Profile	Square Edge	Cartons per Pallet	50	52	40	48
Warranty	15 Year Limited Commercial	Square Feet per Pallet	2,100.0 SF	2201.7 SF	2160.0 SF	2599.1 SF
		Pallets per Container	20	20	20	18
		Square Feet per Container	42,000.0 SF	44,033.5 SF	43,200.0 SF	46,784.6 SF

TEST METHOD		
	Requirements	Results
ASTM F1700 STANDARD SPECIFICATION FOR SOLID VINYL FLOOR TILE	Class III - Print Film Vinyl Tile, Type B - Embossed Surface	Meets Requirements
ASTM F137 Flexibility	25.4 mm Mandrel	Meets Requirements
ASTM F386 Flooring Thickness	as specified +/- 0.005 in. (0.13)	Meets Requirements
ASTM F410 Wear Layer Thickness	Commercial 20 Mils (0.020 in. or 0.5 mm) min.	Meets Requirements
ASTM F925 Resistance to Chemicals	Passes No or slight discoloration	Meets Requirements
ASTM F1514 Heat Color Stability	Passes Delta E ≤ 8.0	Meets Requirements
ASTM F1515 Light Color Stability	Passes Delta E ≤ 8.0	Meets Requirements
ASTM F1914 Short Term Indentation	Avg. Residual Indentation < 8.0% Max. Residual Indentation < 10.0%	Meets Requirements
ASTM F2055 Size	Max. +/- 0.016 in. (0.4 mm) per linear ft. (305 mm)	Meets Requirements
ASTM F2055 Squareness	Max. 0.01 In. (0.25 mm)	Meets Requirements
ASTM F2199 Dimensional Stability	Max 0.02 in. (0.5 mm) per linear ft.	Meets Requirements
ASTN F2199 Curling	Max 0.079 in. (2.0 mm)	Meets Requirements
PERFORMANCE TEST DATA		
ASTM E648 (NFPA 253) Critical Radiant Flux	Class 1 ≥ 0.45 W/cm2	Meets Requirements
ASTM E662 (NFPA 258) Smoke Density	< 450 Flaming / Non-Flaming	Meets Requirements
ASTM F970 Static Load Limit	250 psi Passes Commercial Requirement	Meets Requirements
ASTM F970 Static Load Limit	1,200 psi Maximum at 0.005 Residual Indentation	Meets Requirements
ASTM D2047 Slip Resistance	≥ 0.6 DCOF - ADA Compliant	Meets Requirements
SUSTAINABILITY TEST DATA		
FloorScore Certified	Yes	Meets Requirements
LEED Contribution MR Credit	Building Product Disclosure - Environmental Product Declaration	Meets Requirements
LEED Contribution MR Credit	Building Product Disclosure, Material Ingredients - Health Product Declaration	Meets Requirements
LEED Contribution EQ Credit	Low-Emitting Materials - FloorScore (CPDH Method v1.2-2017)	Meets Requirements
Recycled Content	100% Post Industrial	