

PRODUCT DETAILS					
Overall Product Thickness	2.5 mm (0.1 In.)	Plank / Tile Size	7" x 48" (177.8 mm x 1219.2 mm)	18" x 36" (457.2 mm x 914.4 mm)	23.6" x 23.6" (600 mm x 600 mm)
Wear Layer Thickness	0.5 mm (20mil)	Pieces per Carton	18	12	14
Finish	Uthethane with Ceramic Bead	Square Feet per Carton	42 SF	54 SF	54.15
Warranty	15 Year Limited Commercial	Carton Weight	34.5 Lbs. (15.7 Kg)	44.1 Lbs. (20 Kg)	46.3 Lbs. (22 Kg)
		Cartons per Pallet	50	40	48
		Square Feet per Pallet	2,100 SF	2,160	2,599.15
		Pallets per Container	20	20	18.00
		Square Feet per Container	42,000 SF	43,200 SF	46,784.64

TEST METHOD		
	Requirements	Results
ASTM F1700 STANDARD SPECIFICATION FOR SOLID VINYL FLOOR TILE	Class III - Print Film Vinyl Tile, Type B - Embossed Surface	Meets Requirements
ASTM F137 Flexibility	25.4 mm Mandrel	Meets Requirements
ASTM F386 Flooring Thickness	as specified +/- 0.005 in. (0.13)	Meets Requirements
ASTM F410 Wear Layer Thickness	Commercial 20 Mils (0.020 in. or 0.5 mm) min.	Meets Requirements
ASTM F925 Resistance to Chemicals	Passes No or slight discoloration	Meets Requirements
ASTM F1514 Heat Color Stability	Passes Delta E ≤ 8.0	Meets Requirements
ASTM F1515 Light Color Stability	Passes Delta E ≤ 8.0	Meets Requirements
ASTM F1914 Short Term Indentation	Avg. Residual Indentation < 8.0% Max. Residual Indentation < 10.0%	Meets Requirements
ASTM F2055 Size	Max. +/- 0.016 in. (0.4 mm) per linear ft. (305 mm)	Meets Requirements
ASTM F2055 Squareness	Max. 0.01 In. (0.25 mm)	Meets Requirements
ASTM F2199 Dimensional Stability	Max 0.02 in. (0.5 mm) per linear ft.	Meets Requirements
ASTN F2199 Curling	Max 0.079 in. (2.0 mm)	Meets Requirements

**PERFORMANCE TEST DATA**

<b>ASTM E648 (NFPA 253) Critical Radiant Flux</b>	Class 1 $\geq 0.45$ W/cm <sup>2</sup>	Meets Requirements
<b>ASTM E662 (NFPA 258) Smoke Density</b>	< 450 Flaming / Non-Flaming	Meets Requirements
<b>ASTM F970 Static Load Limit</b>	250 psi Passes Commercial Requirement	Meets Requirements
<b>ASTM F970 Static Load Limit</b>	1,200 psi Maximum at 0.005 Residual Indentation	Meets Requirements
<b>ASTM D2047 Slip Resistance</b>	$\geq 0.6$ DCOF - ADA Compliant	Meets Requirements

**SUSTAINABILITY TEST DATA**

<b>FloorScore Certified</b>	Yes	Meets Requirements
<b>LEED Contribution MR Credit</b>	Building Product Disclosure - Environmental Product Declaration	Meets Requirements
<b>LEED Contribution MR Credit</b>	Building Product Disclosure, Material Ingredients - Health Product Declaration	Meets Requirements
<b>LEED Contribution EQ Credit</b>	Low-Emitting Materials - FloorScore (CPDH Method v1.2-2017)	Meets Requirements
<b>Recycled Content</b>	100% Post Industrial	